




# SAFETY DATA SHEET (SDS)

## Silver Brazing Alloys

<b>1</b>	<b>Identification</b>
<b>1.1</b>	<b>GHS product identifier</b> <b>Trade names:</b> 1003 Bare, 1003 FC, 1004 Bare, 1004 FC, 1005 Bare, 1005 FC, 1018 FC, 1050 FC, 1080 FC, 2550 Bare, 2556 Bare, SF 110, Trialloy (1-2-1)
<b>1.2</b>	<b>Other means of identification:</b> N. App.
<b>1.3</b>	<b>Recommended use of the chemical and restriction on use:</b> Silver brazing, flux coated, or bare silver alloy for torch brazing or torch soldering. Do not weld near flammable or combustible materials.
<b>1.4</b>	<b>Supplier:</b> Arctec Alloys Limited 4304 - 10 St. N.E., Calgary, Alberta, T2E 6K3 Phone: (403) 250-9355
<b>1.5</b>	<b>Emergency phone number:</b> HealthLink 24/7 (Alberta Health Services): 800-624-2356 Out-of-province or internet phone users: 866-408-5465
<b>2</b>	<b>Hazard(s) Identification</b>
<b>2.1</b>	<b>Classification of the substance or mixture:</b> Class: Carcinogenicity <span style="float: right;">Category: 1A</span> Class: Reproductive Toxicity <span style="float: right;">Category: 2</span> Class: Germ Cell Mutagenicity <span style="float: right;">Category: 1B</span> Class: Respiratory Sensitization <span style="float: right;">Category: 1</span> Class: Skin Sensitization <span style="float: right;">Category: 1</span> Class: Specific Target Organ Toxicity – (repeated exposure) <span style="float: right;">Category: 1</span> Target Organs: Lungs, Kidneys, Liver, Respiratory System, Nerves, Blood, Eyes, Skin  
<b>2.2</b>	<b>GHS label elements:</b> <b>Signal Word:</b> Danger <b>Hazard Statements:</b> H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H340 May cause genetic defects. H350 May cause cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long-lasting effects.  <b>Precautionary Statements:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P283 Wear fire resistant or flame retardant clothing.  
 P284 In case of inadequate ventilation wear respiratory protection.  
**Response Statements:**  
 P308 + P313 If exposed or concerned, get medical advice/attention.  
 P314 Get medical attention if you feel unwell.  
 P332 + P352 IF SKIN irritation occurs: Wash with plenty of water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
 P337 + P313 If eye irritation persists: Get medical attention.

**2.3 Other hazards which do not result in classification:**  
 Persons with pacemakers should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device.  
 Heat: Spatter and melting metal can cause burn injuries and start fires.  
 Radiation: Arc rays can severely damage eyes or skin.  
 Electricity: Electric shock can kill.

**3 Composition/Information on Ingredients**

Chemical Name	SDS# and Weight %													CAS	EINECS
	1003 Bare	1003 FC	1004 Bare	1004 FC	1005 Bare	1005 FC	1018 FC	1050 FC	1080 FC	2250 Bare	2556 Bare	SF 110	Tri alloy		
Boric Acid	<0.1	<0.1	<0.1	0.1-2	<0.1	0.1-2	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	10043-35-3	233-139-2
Cadmium	10-30	10-30	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	10-30	7440-43-9	231-152-8
Copper	10-30	10-30	10-30	15-40	10-30	10-30	40-70	30-60	40-70	10-30	10-30	<0.1	10-30	7440-50-8	231-159-6
Iron	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	1-5	<0.1	<0.1	<0.1	<0.1	<0.1	7439-89-6	231-096-4
Manganese	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	1-5	<0.1	<0.1	<0.1	<0.1	<0.1	7439-96-5	231-105-1
Nickel	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	10-30	1-5	<0.1	1-5	<0.1	<0.1	1-5	7440-02-0	231-111-4
Potassium bifluoride	<0.1	<0.1	<0.1	1-11	<0.1	1-11	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	7789-29-9	232-156-2
Potassium pentaborate	<0.1	<0.1	<0.1	1-11	<0.1	1-11	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	12229-13-9	602-489-1
Potassium tetraborate	<0.1	<0.1	<0.1	1-11	<0.1	1-11	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	12228-88-5	682-302-8
Silver	30-60	30-60	40-70	30-60	40-70	30-60	<0.1	<0.1	<0.1	40-70	40-70	1-5	40-70	7440-22-4	231-131-3
Tin	<0.1	<0.1	<0.1	<0.1	1-5	1-11	<0.1	1-5	<0.1	<0.1	1-5	60-100	<0.1	7440-31-5	231-141-8
Zinc	10-30	10-30	15-40	15-40	10-30	10-30	40-70	40-70	40-70	10-30	10-30	<0.1	10-30	7440-66-6	7440-66-6

**4 First Aid Measures**

**4.1 Description of necessary first-aid measures:**

<b>Inhalation:</b>	If breathing has stopped, perform artificial respiration. If no detectable pulse, begin Cardio Pulmonary Resuscitation (CPR). Obtain emergency medical assistance immediately! If breathing is difficult, provide fresh air and call Poison Center/doctor.
<b>Eye:</b>	For radiation burns due to arc flash, see doctor. To remove dusts or fumes, flush cautiously with water for at least fifteen minutes. Remove contact lenses if present and easy to do. If irritation persists, see a doctor.
<b>Skin:</b>	For skin burns from arc radiation, promptly flush with cool water. Get medical attention for burns or irritations that persist. To remove dust or particles wash with water.
<b>Ingestion:</b>	Not applicable
<b>Electric Shock:</b>	Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. If not breathing, begin artificial respiration. If no detectable pulse, begin Cardio Pulmonary Resuscitation (CPR). Obtain emergency medical assistance immediately!

**4.2 Most important symptoms/effects, acute and delayed:** Asthma, chest pain, cough, wheezing, chest tightness.

**4.3 Indication of immediate medical attention and special treatment needed:** Asthma, chest pain, cough, wheezing, chest tightness. For severe inhalation exposure, watch person for at least 48 hours in case pulmonary oedema

	develops.			
<b>4.4</b>	<b>General:</b> Move to fresh air and get medical assistance.			
<b>5</b>	<b>Fire Fighting Measures</b>			
<b>5.1</b>	<b>Suitable extinguishing media:</b> No specific recommendations for welding consumables. Welding arcs and sparks can ignite combustible and flammable materials. Use the extinguishing media recommended for the burning materials and fire situation.			
<b>5.2</b>	<b>Specific hazards arising from the substance or mixture:</b> Depends on burning materials. Smoke may contain toxic metal fumes such as chromium, nickel, manganese from welding consumables.			
<b>5.3</b>	<b>Special protective equipment or actions for fire-fighters:</b> Wear self-contained breathing apparatus.			
<b>6</b>	<b>Accidental Release Measures</b>			
<b>6.1</b>	<b>Personal precautions, protective equipment and emergency procedures:</b> Refer to Section 8			
<b>6.2</b>	<b>Environmental precautions:</b> Refer to Section 13			
<b>6.3</b>	<b>Methods and materials for containment and cleaning up:</b> Place in suitable container for appropriate disposal.			
<b>7</b>	<b>Handling and Storage</b>			
<b>7.1</b>	<b>Precautions for safe handling:</b> Wear gloves when handling brazing consumables. Avoid exposure to fume and dust. Retain all warning and identity labels.			
<b>7.2</b>	<b>Conditions for safe storage, including any incompatibilities:</b> Store in a dry place. Keep separate from chemical substances such as acids and strong bases, which could cause chemical reactions.			
<b>7.3</b>	<b>Specific end use(s):</b> Welding.			
<b>8</b>	<b>Exposure Controls/Personal Protection</b>			
<b>8.1</b>	<b>Control parameters:</b>			
	Exposure limits: Use industrial hygiene monitoring equipment to ensure that exposures do not exceed applicable regulatory exposure limits (see below). ACGIH TLVs are recommended limits – not regulatory limits. Unless noted, all values apply to 8-hour time weighted average exposures (TWA).			
	<b>Substance</b>	<b>CAS#</b>	<b>ACGIH TLV mg/m<sup>3</sup></b>	<b>Alberta OEL mg/m<sup>3</sup></b>
	Borates, tetra sodium salts	1303-86-2	N.Av.	1
	Borate compounds, Inorganic, Inhalable	1303-96-4 1330-43-4 10043-35-3 12179-04-3	2	N.Av.
	Boron oxide	1303-86-2	10	10
	Cadmium and compounds, as Cd	7440-43-9	0.01 0.002 (R)	0.01 0.002 (R)
	Copper (fume)	7439-89-6	0.2	0.2
	Iron oxide	1309-37-1	5(R)	5(R)
	Manganese	7439-96-5	0.02(R), 0.1(I)	0.2
	Nickel compounds - Soluble inorganic	7440-02-0	0.1(I)	0.1
	Nickel metal	7440-02-0	1.5(I)	1.5
	Potassium hydroxide	1310-58-3	2 (C)	2 (C)
	Silver - Metal, dust and fume	7440-22-4	0.1	0.1
	Silver - Soluble compounds, as Ag	7440-22-4	0.01	0.01
	Tin - Metal	7440-31-5	2	2
	Tin - Oxide and inorganic compounds	7440-31-5	2	2
	Tin - Organic compounds, as Sn	7440-31-5	0.1	0.1
	Zinc oxide (fume)	1314-13-2	2 (R)	2 (R)
	ACGIH TLVs: Threshold Limit Values according to American Conference of Governmental Industrial Hygienists. Alberta OELs: Alberta Occupational Exposure Limits BC ELs: British Columbia Exposure Limits (R) Respirable fraction, (I) Inhalable fraction. If no (R) or (I) designation is shown, values refer to total particulate.			
<b>8.2</b>	<b>Appropriate engineering controls:</b> Ensure sufficient local exhaust and general ventilation to keep exposures to brazing fumes and gases below regulatory exposure limits. Use special care when welding painted or coated			

	steels since hazardous substances from the coating may be emitted. If coating contains lead or mercury, remove before welding.	
<b>8.3</b>	<b>Individual protection measures:</b> Wear hand, head, eye, hearing and body protection such as welder's gloves, helmet or face shield with filter lens, ear muffs/plugs, safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry. Check condition of protective clothing and equipment on a regular basis. Use respiratory protection (P100 air purifying or supplied air respirator as appropriate) where ventilation is not sufficient to keep exposures below regulatory limits. Never use air purifying respirators in oxygen deficient atmospheres.	
<b>9</b>	<b>Physical and Chemical Properties</b>	
<b>9.1</b>	Information on basic physical and chemical properties:	
	Appearance, colour:	Solid (wire or rod), non-volatile with varying color.
	Physical state:	Solid
	Auto-ignition temperature:	Not available
	Decomposition temperature:	Not available
	Evaporation rate:	Not applicable
	Explosive properties:	Not applicable
	Flammability (solid, gas):	Not applicable
	Flash point:	Not applicable
	Initial boiling point and boiling range:	Not available
	Melting point:	>1300 °C / >2300 °C
	Freezing Point:	>1300 °C / >2300 °C
	Odour:	None
	Odour threshold:	Not applicable
	Oxidising Properties:	Not applicable
	Partition coefficient (n-octanol/water):	Not available
	pH:	Not available
	Relative density:	Not available
	Solubility:	Not applicable
	Upper / Lower flammability or explosive limits:	Not applicable
	Vapour density:	Not applicable
	Vapour pressure:	Not applicable
	Viscosity:	Not applicable
<b>10</b>	<b>Stability and Reactivity</b>	
<b>10.1</b>	<b>Reactivity:</b> May react with acids and strong bases producing gas.	
<b>10.2</b>	<b>Chemical stability:</b> This product is stable under normal conditions.	
<b>10.3</b>	<b>Possibility of hazardous reactions:</b> May react with acids and strong bases producing gas.	
<b>10.4</b>	<b>Conditions to avoid:</b> Wet, acids, bases	
<b>10.5</b>	<b>Incompatible materials:</b> Acids, bases	
<b>10.6</b>	<b>Hazardous decomposition products:</b> When this product is used in a brazing process, hazardous decomposition products include those from the volatilization, reaction or oxidation of the materials listed in Section 2. Carbon oxides, nitrogen oxides and ozone may also be produced. Allow cleaning solvents to dry off work before brazing. Thermal decomposition products of halogenated cleaning solvents may be highly poisonous.	
<b>11</b>	<b>Toxicological Information</b>	
<b>11.1</b>	Likely Routes of Exposure: <u>x</u> Inhalation <u>x</u> Skin contact <u>x</u> Eye contact <u>  </u> Ingestion	
	<b>Acute Toxicity:</b> Overexposure to welding fumes can cause irritation of eyes, nose, throat and lungs. It may result in metal fume fever (chills, fever, upset stomach, vomiting, throat irritation, muscle aches), dizziness, nausea, dryness or irritation of the nose, throat, lungs and eyes. Airway restriction with tightening of chest and cough may occur. Excessive exposure may cause delayed pulmonary oedema (after 24-48 hours), which may be fatal.	
	Skin corrosion/irritation: Irritation	
	Serious eye damage/ irritation: Irritation	

Respiratory and/or skin sensitization: Yes				
Germ cell mutagenicity: Not available				
Genotoxicity: Yes				
Carcinogenicity: Yes				
Reproductive toxicity: Yes				
STOT – Single Exposure: Not available				
STOT – Repeated Exposure: Yes – lungs and skin				
Harmful if inhaled: Yes				
Single exposure: Yes				
Aspiration hazard: No				
Repeated exposure: Yes				
Interactive effects: Not available				
Chemical Name	CAS Number	EINECS Number	LC50, inhalation	LD50, oral
Boric Acid	10043-35-3	233-139-2	N.Av.	2660 mg/kg, rat
Cadmium	7440-43-9	231-152-8	4.2 mg/cu m, rat, 4H (based on conversion from 30 minute data)	225 mg/kg, rat
Copper	7440-50-8	231-159-6	N.Av.	472 mg/kg, rat
Iron	7439-89-6	231-096-4	N.Av.	750 mg/kg, rat
Manganese	7439-96-5	231-105-1	>1500 mg/m3	9000 mg/kg, rat
Nickel	7440-02-0	231-111-4	N.Av.	>9000 mg/kg, rat
Potassium bifluoride	7789-29-9	232-156-2	N.Av.	160 mg/kg, rat
Potassium pentaborate	12229-13-9	602-489-1	N.Av.	N.Av.
Potassium tetraborate	12228-88-5	682-302-8	N.Av.	>2000 mg/kg, rat
Silver	7440-22-4	231-131-3	N.Av.	>5000 mg/kg, rat
Tin	7440-31-5	231-141-8	N.Av.	2207 mg/kg
Zinc	7440-66-6	7440-66-6	N.Av.	650 mg/kg, rat
<p><b>Chronic Toxicity:</b> Repeated exposure to welding fumes may cause a progressive lung disease (mixed-dust pneumoconiosis) which impairs breathing. Boron compounds can cause irritation of the eyes, nose, throat and lungs. No significant long term effects were found for humans, but some evidence was found of reproductive toxicity in test animals. Cadmium is a human carcinogen (IARC Group 1, Carcinogenic to Humans; and ACGIH A2, Suspected Human Carcinogen). Inhalation of cadmium fume can cause lung irritation, possibly leading to delayed pulmonary oedema, which may be fatal. Intake of cadmium into the body by any route may damage the kidneys. Cadmium remains in the body for many years, only slowly being metabolized and excreted. Inhalation of copper fume may cause metal fume fever and nasal congestion, ulceration and perforation. Exposure to fluorides can cause eye, nose and throat irritation and fluorosis, a potentially crippling bone disease. Although inhalation of iron is not especially toxic in comparison to many other metals, it will deposit in the lungs possibly causing siderosis. This may lead to breathlessness, coughing and decreased lung function. Deposition can also occur in the eyes, and in some cases may lead to cataracts and night blindness. Manganese exposure can cause neurological damage including: slowness, changes in gait, changes in handwriting, muscle spasm, cramps, tremors, slurred speech, and behavioral changes. These may become permanent with long term overexposure. Allergic asthma and bronchitis may occur due to exposure to nickel compounds. CERTAIN NICKEL COMPOUNDS ARE CONFIRMED OR SUSPECTED CARCINOGENS. Kidney and liver damage may also occur. Nickel compounds can cause allergic skin rash. Overexposure to silver can cause argyria, which can turn the skin a blue or grey color. Exposure to tin dust and fume can result in irritation of the eyes and lungs. Deposition of tin in the lungs is not thought to cause serious health effects. Zinc fume exposure may cause metal fume fever with cough, chills, fever, shortness of breath, chest pain, nausea and vomiting.</p>				
<b>12</b>	<b>Ecological Information</b>			
<b>12.1</b>	<b>Toxicity:</b> Not available			
<b>12.2</b>	<b>Persistence and degradability:</b> Not available			
<b>12.3</b>	<b>Bioaccumulative potential:</b> Not available			
<b>12.4</b>	<b>Mobility in soil:</b> Not available			
<b>12.5</b>	<b>Results of PBT and vPvB assessment:</b> Not available			

<b>12.6</b>	<b>Other adverse effects:</b> Not available
<b>12.7</b>	<b>Other:</b> Brazing consumables could degrade / weather into other forms. Avoid exposure to conditions that could lead to accumulation in soils or groundwater. Nickel is harmful to the environment, harmful to aquatic organisms, and may cause long-term adverse effects in the aquatic environment.
<b>13</b>	<b>Disposal Considerations</b>
<b>13.1</b>	<b>Disposal and waste treatment methods:</b> Reuse or recycle where possible. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, provincial and local regulations. Use recycling procedures if available. <b>USA RCRA:</b> Unused products or product residue containing cadmium and silver are considered hazardous wastes if discarded: RCRA Hazardous Waste Codes D006 and D011 respectively. Residues from brazing consumables and processes could degrade and accumulate in soils and groundwater. See also Section 8 for exposure controls while handling.
<b>14</b>	<b>Transportation Information</b>
<b>14.1</b>	<b>UN number:</b> Not applicable
<b>14.2</b>	<b>UN proper shipping name:</b> Not applicable
<b>14.3</b>	<b>Transport hazard class(es):</b> Not applicable
<b>14.4</b>	<b>Packing group:</b> Not applicable
<b>14.5</b>	<b>Environmental hazards:</b> Not applicable
<b>14.6</b>	<b>Special precautions for user:</b> Not applicable
<b>14.7</b>	<b>Transport in bulk according to Annex II of MARPOL and the IBC Code:</b> Not applicable
<b>15</b>	<b>Regulatory Information</b>
<b>15.1</b>	<b>Safety health and environmental regulations /legislation specific for the substance or mixture (applies to the airborne emissions during use).</b> <b>Canada:</b> Class: Carcinogenicity Category: 1A Class: Reproductive Toxicity Category: 2 Class: Germ Cell Mutagenicity Category: 1B Class: Respiratory Sensitization Category: 1 Class: Skin Sensitization Category: 1 Class: Specific Target Organ Toxicity – (repeated exposure) Category: 1 Target Organs: Lungs, Kidneys, Liver, Respiratory System, Nerves, Blood, Eyes, Skin Canadian Environmental Protection Act (CEPA): All constituents of this product are on the Domestic Substances List (DSL). <b>USA:</b> Under the OSHA Hazard Communication Standard, this product is considered hazardous. This product contains or produces a chemical known to the state of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code § 25249.5 et seq.) United States EPA Toxic Substance Control Act: All constituents of this product are on the TSCA inventory list or are excluded from listing. <b>CERCLA/SARA Title III Reportable Quantities (RQs):</b> Product is a solid solution in the form of a solid article: Cadmium RQ 10 lbs; Nickel RQ 100 lbs; Manganese RQ N.Av.; Copper RQ 5000 lbs; Silver RQ 1000 lbs; Zinc RQ 1000 lbs. Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center and to your Local Emergency Planning Committee. The following metallic components are listed as SARA 313 “Toxic Chemicals” and potentially subject to annual SARA 313 reporting (shown with de minimis concentrations): cadmium, 0.1%; manganese, 1.0%; nickel, 0.1%; copper, 1.0%; silver, 1.0%; zinc, 1.0%. See Section 3 for weight % in product.
<b>15.2</b>	<b>Other:</b> Read and understand the manufacturer's instructions, your employer's safety practices and the health and safety instructions on the label. Observe all applicable regulations. Take precautions when brazing, and protect yourself and others. <b>WARNING:</b> Brazing fumes and gases are hazardous to your health and may damage

	lungs and other organs. Use adequate ventilation. ELECTRIC SHOCK can kill. ARC RAYS and SPARKS can injure eyes and burn skin. Wear correct hand, head, eye and body protection.
<b>16</b>	<b>Other Information</b>
<b>16.1</b>	<p><b>USA:</b> American National Standard Z49.1. "Safety in Welding and Cutting", ANSI/AWS F1.5. Methods for Sampling and analyzing Gases from Welding and Allied Processes., ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes", AWSF3.2M/F3.2 "Ventilation Guide for Weld Fume", American Welding Society, 550 North Le Jeune Road, Miami Florida, 33135. Safety and Health Fact Sheets available from AWS at <a href="http://www.aws.org">www.aws.org</a>  OSHA Publication 2206 (29 C.F.R. 1910), U.S. Government Printing Office, Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954.  American Conference of Governmental Hygienists (ACGIH), Threshold Limit Values and Biological Exposure Indices, 6500 Glenway Ave., Cincinnati, Ohio 45211, USA.  NFPA 51B "Standard for Fire Prevention During Welding, Cutting and Other Hot Work" published by the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169</p> <p><b>Canada:</b> CSA Standard CAN/CSA-W117.2-01 "Safety in Welding, Cutting and Allied Processes"</p>
<b>16.2</b>	<p>This SDS has been prepared by Arctec Alloys Limited based on information obtained from sources believed to be accurate and reliable. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or completeness thereof. The conditions or methods of handling, storage, use and disposal of the product are beyond the control and knowledge of Arctec Alloys Limited. For this and other reasons Arctec Alloys Limited does not assume responsibility, and expressly disclaims liability for loss, damage or expense arising from it or in any way connected with the handling, storage, use or disposal of the product.</p>